

# PRODUCT DATA SHEET **POLYETHYLENE FT6237** LDPE for Film (Non- Food Application)

#### DESCRIPTION

**FT6237** is a Low Density Polyethylene for Film extrusion produced by high pressure Tubular Technology. This product is developed for Blown film application covering areas like Lamination film, Air bubble film and PE foam. It may contain traces of Silane, Butyl Acrylate and Octadiene and this grade is for non-food application

FT6237 contains no additive.

CAS-No. 9002-86-4

# **APPLICATIONS**

FFS Bags Lamination Shopping Bags/ Air bubble Films

# **KEY FEATURES**

Excellent process ability Excellent Sealing

### **PHYSICAL PROPERTIES**

Property Density Melt Flow Rate (190°C/2.16kg) Melting Temperature Vicat Softening Point A50 (10 N)

\* Typical properties and data should not be used for specification work

# **FILM PROPERTIES<sup>1</sup>**

Property**	Typical Value*	Test Method
Tensile Strength at Break (MD/TD)	25/20 MPa	ISO 527-3
Elongation at Break (MD/TD)	300/600 %	ISO 527-3
Tensile Modulus (1 % Secant) (MD/TD)	180/190 MPa	ASTM D 882
Coefficient of Friction	0.6	ASTM D 1894
Gloss at 60°C (of arc)	90	ASTM D 2457
Haze	7 %	ASTM D 1003
Dart Drop	100 g	ASTM D 1709/A
Tear Strength (MD/TD)	2/2 N	ASTM D 1922

<sup>1</sup> Film properties: 40µm, BUR=3:1, Die gap 1.2mm

Borouge Pte Ltd 1 George Street, #18-01 Singapore 049145 T +65 6275 4100 F +65 6377 1233 PE Foam Shrink Film Non-Food Packaging

Excellent Optical Properties Mono Layer & Co-extrusion Film

Typical Value\* 923 kg/m3

2.0 g/10min

111 °C

95 °C

**Test Method** ASTM D 792 ASTM D1238 ISO 11357/03 ISO 306



\* Typical properties and data should not be used for specification work

\*\* The film properties are dependent on extrusion conditions.

# PROCESSING CONDITIONS

FT6237 can be processed in most types of blown film equipment such as LDPE, LLDPE or HDPE extruders.

Recommended processing conditions:

Melt temperature	160 - 180°C
Die gap	>1.0 mm
FLH	>2 DD
BUR	>2:1

## FOOD CONTACT REGULATIONS

FT6237 is a non-food grade

#### STORAGE

This product should be stored in dry conditions at temperature bellow 50°C and protected from UV-light. Improper storage can initiate degradation, which results in odour generation and colour changes and can have negative effects on physical properties of this product.

More information on storage can be found in Safety Information Sheet (SIS) for this product.

#### SAFETY

The product is not classified as a hazardous mixture.

Dust and fines from the product carry a risk of dust explosion. All equipment should be properly earthed. Inhalation of dust should be avoided as it may cause irritation of the respiratory system. Small amounts of fumes are generated during processing of the product. Proper ventilation is therefore required.

Please see our Safety Information Sheet (SIS) for details on various aspects of safety, recovery and disposal of the product, for more information contact your Borouge representative.

#### RECYCLING

The product is suitable for recycling using modern methods of shredding and cleaning. In-house production waste should be kept clean to facilitate direct recycling.

#### **RELATED DOCUMENTS**

The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.

Safety Information Sheet Statement on chemicals, regulations and standards

#### **STANDARDS**

Borouge is certified to various ISO standards, please refer to Borouge.com for more information.





#### DISCLAIMER

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however, we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borouge makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borouge's products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

Borstar® is a trademark of the Borealis group.

Jan 2018

Borouge Pte Ltd 1 George Street, #18-01 Singapore 049145 T +65 6275 4100 F +65 6377 1233

Borouge is a joint venture of ADNOC and Borealis

